


GENERAL NOTES

- 1) ALL STRUCTURAL STEELWORK TO BE GRADE 43C.
- 2) STEELWORK TO BE WIRE BRUSHED PRIOR TO PAINT APPLICATION.
- 3) APPLY ONE COAT OF GREY DIOXIDE PRIMER.
- 4) APPLY ONE COAT OF SILVER ALUMINUM PAINT.
- 5) ALL SHOP WELDS TO BE 8MM FILLET WELDS U.S.N.
- 6) BOLTS ARE GALVANIZED GRADE 4.6. & GRADE 8.8
- 7) ALL SECTION SIZES TO BE AS SPECIFIED ON DRAWING.
- 8) THIS DRAWING TO BE READ IN CONNECTION WITH ALL OTHER RELEVANT DRAWINGS.

<p>All Dimensions in mm unless otherwise specified All works to be carried out in accordance with local authority regulations Use figured dimensions only do not scale from the drawing All reinforced concrete works is to be in accordance with S.E's details. LEVELS in meters Ground to be well tested during excavations.</p>	<p>Proposed 50 cubic metres tank on a 10 metres high tower in SKUMA village in Ngaremara .</p> <p>October 2022</p>	 <p>Merti Integrated Development Programme Collective Action: Better Society</p>
--	--	--